

iKERN-4052-A610

4U Industrial Rackmount Computer



Specifications

CPU

- Intel® Core™ i3/i5/i7/i9/Pentium/Celeron 12th/13th/14th Generation:

i9-14900	i7-14700	i5-14500	i3-14100	i9-13900	i7-13700	i5-13500	i3-13100
5.8 GHz	5.4 GHz	2.6 GHz	3.5 GHz	5.6 GHz	5.2 GHz	2.5 GHz	3.4 GHz
i9-12900	i7-12700	i5-12500	i3-12100	G6900E	G7400E		
5.1 GHz	4.9 GHz	3.0 GHz	3.3 GHz	3.6 GHz	3.0 GHz		

Memory

- 2x 288-pin DIMM sockets
- Supports up to 96GB DDR5 4800/5600 MHz, unbuffered, None ECC

Chipset

- Intel® H610

Graphic

- Integrated in CPU Intel® UHD Graphics 770 / 730 / 710
Support DirectX 12, OpenGL 4.5, OpenCL 3.0, Triple View
- Video ports: HDMI, 2x Display Port, VGA
- DP++ 1.4a: resolution up to 4096x2160 @ 60Hz
- HDMI 2.0b: resolution up to 4096x2160 @ 60Hz
- VGA: resolution up to 1920x1200 @ 60Hz

Ethernet

- 1x Realtek RTL8125BG 2.5 Gigabit Ethernet Controller, supports PoE
- 1x Intel® i219-V Gigabit Ethernet Controller

Storage / Drive Bays / Slots

- 2x 3.5"
- 3x 5.25" (optional pre-assembled with DVDRW)
- 1x 3042/2260/2280/22110 M.2 M-Key, supports SSD

RAID / SATA

- 4x SATA 3.0

Expansion Slots

- 1x PCIe x16 Gen 5
- 1x PCIe x4 Gen 3
- 1x PCIe x1 Gen 3
- 4x PCI 32-bit/33 MHz

Front I/O

- 2x USB 2.0

Rear I/O

- 2x DP, 1x HDMI, 1x VGA, 2x RJ45 LAN, 2x DB9 RS232/422/485
- 2x USB 3.2 Gen2, 2x USB 2.0, 1xPS/2 (KB/M)
- Line-in/out, Mic-in

Other Internal Connectors / Functions

- 4x RS232, 2x USB 3.2 Gen1, 1x USB 2.0 Vertical Type-A
- 1x 16-bit GPIO, TPM 2.0

Power Supply

- Power input: 500W, 100-240V AC 50~60 Hz, 80 Plus Gold

Cooling

- 1x 120mm, 1x 80mm Cooler

Mechanical

- Heavy Duty Cold Rolled Electroplated Steel
- Mounting: optional slide-rails
- Power / Reset Button in front

Dimensions

- Dimension (W x H x D mm): 483 x 177 x 451 mm
- Weight: 15 kg

Environment

- Operating Temperature: 0°C to 50°C
- Storage Temperature: -20°C to 70°C
- Humidity: 10 ~ 90%, non-condensing

Certifications

- CE

Operating System Support

- Windows 10 / 11 Pro / Windows 10 IoT LTSC / 11 IoT LTSC

Ordering Information

#iKERN-4052-A610