DURABOOK

Mobile Systems











515AB

Specification

Rugged Features	• Drop: 2.5 feet/6 faces	
	Spill-proof keyboard / IP54	
	• Vibration: MIL-STD-810G, Method 514.6, AnnexC Category 4, Fig. 514	4.6C-1
	ASTM 4169-08, Truck Transport, 11.5.2 Random test, Assurance Level	II .
Environment	• Operating: 0~ 45 °C (32~ 113°F) • Humidity: Operating: 5%~95%	• Storage: -40 ~ 71 °C (-40 ~ 159 °F) • Altitude: Operating: 15,000ft
Operating System	Windows 7 Pro/ Windows 8.1 Pro, Window 10	
CPU	Intel 5th Generation i-Core/Pentium CPU	
Memory	• 16GB (Maximum)	
Storage	• Supports 2.5" 7mm SATA3 HDD 500GB~1TB or SSD 128GB~512GB	
Display	• 15.6" Full HD Display, screen resolution 1920 x 1080	
A	High Definition Audio	
Audio	Two speakers, Sound pressure 80dB Audio Jack	
Camera	• Integrated 2 Mega-pixel Web-cam, with Mic x2	
Communication	• Integrated Gigabit Ethernet with RJ45 connector • Bluetooth 4.0 Class 1	• Intel Dual Band Wireless AC 7265
Security	Kensington Lock Hole (clearance) Computrace ready	 Administrator password/ Boot password TPM 2.0 module
Expansion Slots	Built-in SD card reader and supports SDXC card Smart Card Reader x1 / Smart card can be fully inserted	
Standard I/O	• Two USB 2.0 connectors	• Two USB 3.0 connectors
	One Head Phone/MIC combo jack (3.5mm)	• One RJ-45 jack for internal 10/100/1000M bit Ethernet
	One DC-In jack	• One 19 pin HDMI type A connector, resolution up to 4K resolution
	One D-sub 9 pin RS-232 serial port	One 15 pin D-sub VGA port
Battery	Battery life 8.5 hours, battery charging time 3.5 hours	
AC Adaptor	• AC power input:100V-240V,50Hz-60Hz, 65W,output: 19V	
Dimension	• 14.7" x 10.7" x1.1 "/ 375mm (W) x 273 mm (D) x 29.5 mm (H)	
Weight	• 5.73 lbs / 2.6 kg	
Certification	FCC, DOC, CUS, CE, CB	
Green Tech	RoHS Compliant, REACH, Energy Star 6.1 certified, ErP, WEEE	

Accessories







DC 19V 65W power adapter

Lithium Polymer Battery Pack



The specification and pictures are subject to change without notice. All brand names are registered trademarks of their respective owners.

http://IPC2U.de



IPC2U GmbH Frankenring 6 D-30855 Langenhagen

FON +49 511 807 259-0 FAX +49 511 807 259-22 MAIL sales@ipc2U.de